Technical Data Sheet
Dura Tuff

Product Description

Dura Tuff is a thick grooved textured finish, highly resistant to alkalies and adheres perfectly to virtually all kind of surfaces. It helps to disguise imperfections, minor cracks and uneven patches on walls.

Composition

Acrylic Copolymers in emulsion, special inorganic pigments, siliceous aggregates, quartz powder, marble chips, bactericides and various additives.

Recommended Use

Protective and decorative coating for internal and external surfaces such as cement plaster, gypsum, asbestos, wood or concrete castings.

Technical Data

✓ Finish	:	Thick Grooved Texture
✓ Color	:	Base Color.
✓ Specific Gravity Kg/L	:	2.00 ± 0.05
✓ Solids	:	88 ± 2%
✓ Theoretical Spreading Rate	:	70 to 75 Sft per bag of 30 kg
✓ Drying Time @ 30° C	:	Hardens completely within 24 Hours.
		• Touch Dry : 1/2 Hour
		• Dry to recoat : 24 Hours
✓ Recommended (DFT)	:	Approximately 2 mm

Application Method

✓ Application Method	:	Applied by Steel Trowel & Finished by Plastic Trowel.
✓ Thinning (Volume)	:	Ready for use.
✓ Thinner / Cleaner	:	Water
✓ Pot Life @ 30° C	:	N.A.
✓ Mixing Ratio (Volume)	:	N.A.
✓ Recommended System	:	Grooved Textured : 1 Coat Primer: 1 Coat Pure Acrylic Top Coat: 2 Coats

Dura Tuff

TEXTURE COATINGS
PAINTS
WOOD COATINGS
EXPANSION JOINT COVERS

DuraShield Building Systems Pvt. Ltd.
10 Tulip, 10th North South Road
J.V.P.D Scheme, Mumbai 400049. INDIA
Phone: +91 (022) 26256921 / 65223848
Fax: +91 (022) 26200563
Email: sales@durabuildsys.com
Web: www.durashieldbuildingsystems.com

Technical Data Sheet
Dura Tuff

Miscellaneous Data

✓ Flash Point	:	Water
✓ Shelf life @ 30 ° C	:	6 months in original sealed container, with proper storage conditions.

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Note: We warranty the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the rights to change data without prior notice.

TEXTURE COATINGS
PAINTS
WOOD COATINGS
EXPANSION JOINT COVERS

DuraShield Building Systems Pvt. Ltd.
10 Tulip, 10th North South Road
J.V.P.D Scheme, Mumbai 400049. INDIA
Phone: +91 (022) 26256921 / 65223848
Fax: +91 (022) 26200563
Email: sales@durabuildsys.com
Web: www.durashieldbuildingsystems.com